



# SOLID F60HD

## Ideal for:

- > Label batch printing
- > Ticket printing
- > Business and logistics documents
- > Utilities, banks or Government high through-put requirements

## HIGHLIGHTS / FEATURES / SPECIAL ATTRIBUTES

- > Most economical cold fusing printer in its class
- > Prints on paper, PVC, plastic, etc.
- > USB, Ethernet (10/100 Mbit) as standard
- > Laser and matrix printer compatible
- > SAP with the standard PCL5e emulation
- > Perfect control via Status Out
- > Optional IPDS emulation making it the printer of choice for IBM solutions

**HIGH PERFORMANCE,  
IMPRESSIVE COST  
EFFECTIVENESS**



## SOLID F60HD

Inexpensive to purchase, inexpensive to operate: the SOLID F60HD is the most economical printer in its class. As a fast continuous laser printer for medium printing volumes it covers a broad spectrum of deployment areas. The powerful Microplex Controller guarantees connection versatility, functional diversity, easy system integration and high printing performance. Cold fusing via Xenon flash lamps also enables thermally sensitive materials such as plastic or PVC to be used. And fusing is also trouble-free even on thick materials.

**SOLID F60HD****SPECIFICATIONS****Print Engine**

<b>Print technology</b>	LED, OPC xenon flash lamp
<b>Controller</b>	MPC 3.3 with Intel CPU (>2 GHz CISC Processor)
<b>Print speed</b>	3.000 lpm (6 lpi) 59 pages/min. (8.5" form length); 45.5 ppm (11" form length)
<b>Print resolution</b>	max. 600 dpi x 600 dpi
<b>Duty cycle</b>	up to 300.000 pages (based on a using period of 60 month)
<b>Power supply</b>	230V +/-10% /50 Hz
<b>Power consumption</b>	max 4,5 kVA (delivery with 32 Amp. connector)
<b>Acoustic noise</b>	< 55 dBA (Standby), < 65 dBA (Operating)
<b>Dimensions (WxDxH in Inch)</b>	31.7"W x 33.5"D x 49.2"H
<b>Weight</b>	529.11 lbs. (incl. Stacker)
<b>Environment temperature</b>	50 - 86°F
<b>Relative humidity</b>	30 - 80 % (rel., non-condensing)
<b>Interfaces</b>	Serial: USB 2.0 Parallel: IEEE 1284 (Centronics) LAN: Ethernet-Interface 10/100 MBit, bi-directional (TCP/IP)
<b>Memory</b>	RAM: 512MB Flash: 64MB

**MPC 3.3 High-End Print-Controller****Emulations**

MICROPLEX IDOL, HP PCL 5e, Epson FX-80, IBM Proprinter, Diablo 630, µ-Postscript, TIFF

**Optional Emulations**

IPDS, Printronix IGP, PGL, Magnum Code V, Kyocera Prescribe, Express, ZPLII, Datamax, EPL,  
(more emulations on request)

**Barcodes**

PDF 417, EAN 8, 13., 128, add on, 2/5 3-stroke Datalogic, 2/5 3-stroke Matrix, Codabar, Royalbar,  
Planet, Jetcaps (HP/SAP), Code 39, 128 MSI, UPC A, E, Postnet, KIX, USPS One Code

**Optional Barcodes**

QR Code, UPS-Maxicode, Datamatrix, USD5, Aztec-Code, (more barcodes on request)

**Additional functions**

<b>Intelligent barcode generation</b>	on-the-fly in the printer
<b>Format splitting</b>	in several subformats by command
<b>Integrated form management</b>	up to 12 MB flash for forms and fonts inside the printer

**Optional functions****Status-Out**

gives notice of each correctly printed page via interface


**SPS-Control (EMBEDDED INTELLIGENCE - Enabling two-way communication between printer and a PLC)**

integration of the printer into production lines is possible, controlled by SPS-interface.

**Printable Media****Size**

Form length	7" - 24"
With stacker	8" - 14"
Form width	6,5" - 16"
Printable area	14,6"

**Weight** 17-56 lb (60 - 204 g/m<sup>2</sup>)

**Paper Path****Input**

push tractor

**Output**

stacker  
capacity: 3.000 pages (17 lb bond)

The brand names referred to are the registered trademarks of the respective companies. All figures and details in italics and highlighted in color are optional. Technical data is subject to change. The information contained in this specification sheet refers exclusively to the described details and not to warranted characteristics. No guarantee is assumed. The information do not exempt from the obligation for inspection of each respective individual case. Version 21.11.2016



PRINTING TECHNOLOGIES  
ENGINEERED IN GERMANY

www.microplex-usa.com